

FILTER AND MANUFACTURING METHOD THEREOF

INCORPORATION BY REFERENCE

The disclosure of Japanese Patent Application No. 2000-387906 filed on December 20, 2000 including the specification, drawings and abstract is incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

1. Field of Invention

[0001] The invention relates to a filter whose filter portion has a plurality of bag-like members and a manufacturing method of the filter.

2. Description of Related Art

[0002] A schematic drawing of a general filter for an internal combustion engine is shown in Fig. 4. A filter 50 consists of a filter portion 52 for filtering fluid and a flange portion 55 formed at the periphery of the filter portion 52. The filter portion 52 comprises a bellows-type wavy board 53 and a side wall board 54 connected to each side of the wavy board 53. The bellows-type wavy board 53 and side wall boards 54 constitute a series of multiple bag-like members F, with generally triangular sections.

[0003] The bag-like members F are susceptible to deformation in a direction (Y direction) orthogonal to a folding line S because the bag-like members F are formed by the wavy boards 53.

SUMMARY OF THE INVENTION

[0004] The invention thus provides a filter with a filter portion which does not easily deform by improving the strength of the filter.

[0005] A first exemplary aspect of the invention is a filter in which the filter portion comprises a plurality of bag-like members. The bag-like member is formed in a container shape having an opening and the bag-like members are all disposed with intervals therebetween. The periphery of the opening of the bag-like member is supported by a supporting member which interconnects each of the bag-like members.

[0006] According to the first exemplary aspect, the bag-like members are disposed with intervals therebetween, and the periphery of the opening of each bag-like member is supported by the supporting member.

[0007] In the aforementioned exemplary aspect, the bag-like member may be formed such that a centerline thereof is orthogonal to the opening and the shape of the section parallel to the opening forms a circle or polygon. This prevents the bag-like member from

deforming easily due to the fluid passing therethrough and enables a filtering efficiency drop caused by adhesion of adjacent bag-like members to be suppressed.

[0008] Also in the exemplary aspect stated above, the supporting member may be formed such that, on a plane surface of the supporting member, a plurality of straight lines that traverse the supporting member exist thereon without interfering with any of the bag-like members, and each straight line intersects with the other straight lines in at least one place each. By doing so, the straight lines function as a framework (beams) that connects the edges of the supporting member, thereby increasing the strength of the supporting member.

[0009] A second exemplary aspect of the invention is a method for manufacturing the filter explained in the aforementioned exemplary aspect. The manufacturing method comprises a step of preparing a forming die having a forming surface formed in a shape almost identical to that of one side of the filter and a step of laminating fibers over the forming surface of the forming die. This method facilitates the manufacturing of the filter explained in the aspect above.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The above mentioned and other objects, features, advantages, and technical industrial significance of this invention will be better understood by reading the following detailed description of the preferred embodiments of the invention, when considered in connection with the accompanied drawings, in which:

Fig. 1 is a perspective view of a filter according to a first embodiment of the invention;

Fig. 2 is a plan view of the filter;

Fig. 3A is a schematic view showing a manufacturing method of the filter;

Fig. 3B is a longitudinal sectional view of a forming die of the filter; and

Fig. 4 is a perspective view of a conventional filter.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0011] Hereinafter, a filter according to a first embodiment of the invention and a manufacturing method of such a filter will be described referring to Figs. 1 to 3. Fig. 1 is a perspective view of a filter according to the first embodiment and Fig. 2 is a plan view of the filter. Fig. 3A is a schematic view showing a manufacturing method of the filter, and Fig. 3B is a schematic view showing a forming die used in manufacturing the filter.

[0012] As shown in Fig. 1, a filter 1 according to the first embodiment comprises a flat plate member 2 and a plurality of bag-like members 3 connected to the flat plate member. The flat plate member 2 is made of nonwoven fabric and formed, for example, in a

rectangular shape, and a through-hole 2h is formed at a location where the bag-like member 3 is connected.

[0013] The periphery 2e (the outer side of the alternate long and two short dashed line L in Fig. 1) of the flat plate member 2 is used as a flange portion when the filter 1 is set in a housing (not shown in the drawing), and the portion other than the periphery 2e is used as a filter portion for filtering fluid. Hereinafter the periphery 2e of the flat plate member 2 will be referred to as a flange portion 2e.

[0014] The bag-like member 3, which constitutes the filter portion just like the flat plate member 2, is made of nonwoven fabric and formed, for example, in a tapered cylindrical shape. The tip of the bag-like member 3 is covered with a disc cap 3f and an opening 3m is provided at the base end of the bag-like member 3. That is, the bag-like member 3 is formed such that a centerline thereof is orthogonal to an opening 3m and the shape of the section parallel to the opening 3m forms a circle. Further, the opening 3m of the bag-like member 3 is connected to the through-hole 2h of the flat plate member 2. Accordingly, the bag-like member 3 is supported from the periphery by the flat plate member 2 at the position of the opening 3m and bag-like members 3 are connected with each other by the flat plate member 2. That is, the flat plate member 2 stated above functions as the supporting member of the invention.

[0015] As shown in Fig. 2, the aforementioned filter 1 has 18 bag-like members 3 disposed with intervals therebetween on the flat plate member 2. The location of each bag-like member 3 is set as follows. First, imaginary straight lines R, S and T (refer to the dotted lines) that traverse the flat plate member 2 are drawn in a mesh on the flat plate member 2. Then, without interfering with the imaginary straight lines R, S and T, a bag-like member 3 is located within the mesh eyes created by the imaginary straight lines R, S and T.

[0016] In other words, on the flat plate member 2 exist the straight lines R, S and T (refer to the dotted lines) that can traverse the flat plate member 2 without interfering with any of the bag-like members 3, and each straight line R, S and T intersects with the other straight lines in at least one place each.

[0017] Accordingly, when the periphery 2e (flange portion 2e) of the flat plate member 2 of the filter 1 is fixed to a housing, the straight lines R, S and T of the flat plate member 2 function just like a framework (beams) crossing on the inner side of the flange portion 2e. Consequently, the strength of the flat plate member 2 is ensured, thus suppressing deformation of the flat plate member 2 caused by fluid passing through.

[0018] Next, a manufacturing facility for the filter 1 and a method for manufacturing the filter 1 using such a facility will be briefly explained referring to Figs. 3A and 3B.

[0019] A filter manufacturing facility 20 is equipped with a horizontal conveyor (not shown in the drawings) on which a plurality of forming dies 22 (only one die is shown in Fig. 3) are arranged in sequence. The forming die 22 has a forming surface 22f whose shape is identical to that of the face of one side of the filter 1, i.e. the face of one side of the flat plate member 2 and bag-like member 3, and is made of permeable meshed metal.

[0020] A spinning nozzle 24 is provided at a predetermined height above the conveyor. The spinning nozzle 24 is, for example, a nozzle that utilizes a melt-blow method and ejects to the forming surface 22f of the forming die 22 a fiber resin M (hereinafter referred to as the fibers M) ejected from an extruder not shown in the drawings. The fibers M ejected from the spinning nozzle 24, which are in semi-molten state, are laminated over the forming surface 22f to be fused together forming nonwoven fabric. Also, a nozzle utilizing a spin-bonding method may be used as the spinning nozzle 24.

[0021] Next, a manufacturing method of the filter 1 will be described.

[0022] First, the forming die 22 moves in the Y direction. When a tip of the forming die 22 (the left end in Fig. 3A) reaches a location directly below the spinning nozzle 24, the semi-molten fibers M ejected from the spinning nozzle 24 are laminated over the forming surface 22f of the forming die 22. At this time, since the forming die 22 travels in the Y direction with respect to the spinning nozzle 24 at a constant speed, as shown in Fig. 3A, a constant thickness of the semi-molten fibers M is laminated over the forming surface 22f of the forming die 22 in sequence starting from the tip side. Thus laminated fibers M are fused together where they contact each other, forming nonwoven fabric. That is, the nonwoven fabric is formed in a shape of the filter 1 by the forming die 22.

[0023] As stated above, with the manufacturing method comprising the steps of preparing the forming die 22 having the forming surface 22f formed in a shape almost identical to that of one side of the filter 1, and laminating the fibers over the forming surface 22f of the forming die 22, the manufacturing efficiency of the filter 1 is improved.

[0024] The manufacturing method of the filter 1 mentioned above facilitates the manufacturing of the filter 1.

[0025] According to this embodiment, the bag-like members 3 of the filter 1 stated above are all disposed with intervals therebetween, and the peripheries of the openings 3m of respective bag-like members 3 are supported by the flat plate member 2. In other words, each

of the bag-like members 3 is supported from the periphery by the flat plate member 2 at the position of the opening 3m.

[0026] Furthermore, the bag-like member 3 is formed such that the centerline thereof is orthogonal to the opening 3m and the shape of the section parallel to the opening 3m forms a circle. Accordingly, the bag-like member 3 does not easily deform due to fluid passing therethrough, thereby suppressing a filtering efficiency drop caused by adhesion of adjacent bag-like members 3.

[0027] Also, on the flat plate member 2 exist a plurality of straight lines R, S and T that traverse the flat plate member 2 without interfering with any of the bag-like members 3, and each straight line R, S and T intersects with the other straight lines in at least one place each. Because the straight lines that are fixed at both ends do not easily deform due to outer force, when the flange portion 2e of the filter 1 is fixed to a housing, the straight lines R, S and T on the flat plate member 2 of the filter 1 function just like the framework (beams) crossing on the inner side of the flange portion 2e. As a result, the strength of the flat member 2 is ensured and deformation thereof can be suppressed.

[0028] The filter 1 according to this embodiment is an example in which the flat plate member 2 is formed in a rectangular shape, however, the shape of the flat plate member 2 may be changed appropriately according to the shape of the section of the housing to which the corresponding filter 1 is fitted. Also, although the example shows the bag-like member 3 formed in a tapered cylindrical shape, the shape of the bag-like member 3 can be a polyangular cylindrical, conical, polyangular conical, or semispherical shape. Furthermore, the number of the bag-like members 3 connected to the flat plate member 2 may be changed appropriately according to the size of the filter 1.

[0029] The embodiment also shows an example in which the semi-molten fibers M are ejected from the spinning nozzle 24 and laminated over the forming surface 22f of the forming die 22, but a method in which fibers are laminated over the forming surface 22f of the forming die 22 based on the principle of paper milling may also be used.

[0030] Further, although the embodiment shows an example of the filter in which single-layer nonwoven fabric is used, the nonwoven fabric used for the filter can also be double-layer or triple-layer fabric.

[0031] While the invention has been described with reference to preferred embodiments thereof, it is to be understood that the invention is not limited to the preferred embodiments or constructions. To the contrary, the invention is intended to cover various modifications and equivalent arrangements. In addition, while the various elements of the

preferred embodiments are shown in various combinations and configurations, which are exemplary, other combinations and configurations, including more, less or only a single element, are also within the spirit and scope of the invention.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000